

2026	Can-Am 	Formula 1 	GT Coupe 	Stock Car 
Controller				
Weight				
Body Maker / Painter				
Chassis Kit / Builder				
Motor			HO No.	
Pinion / Crown				
Guide Flag				
Rear Wheels & Tires				
Front Tires & Wheels				
Specifications	☐ Total weight - 100 grams minimum ☐ Chassis width - 3.125" maximum ☐ Body width - 3.250" at the wheel arches ☐ Body thickness - .008" top with .007" minimum on sides ☐ F & R track width - 3.125" ☐ Chassis clearance, F & R - .015" / .050" minimum ☐ Front tire diameter - .750" minimum ☐ Front tire width - .225" minimum ☐ Rear tire diameter - .8125" minimum ☐ Rear tire width - .810" maximum ☐ Motor type – JK Hawk Retro / CR 102 ☐ Body height - 1.375" maximum ☐ Front grill - .063" (1/16") except Ti22 ☐ Spoiler size / height - no wider than body; .500" maximum ☐ Driver figure/interior - fully-molded, min.2-color, presentably/realistically painted, no paper and attached to the body-no sagging	☐ Total weight - 100 grams minimum ☐ Chassis width 1.625" max ☐ Minimum wheelbase - 3.750" ☐ Maximum wheelbase - 4.250" ☐ Body thickness - .008" top with .007" minimum on sides ☐ F & R track width - 3.250" ☐ Chassis clearance, F & R - .015" / .040" minimum ☐ Front tire diameter - .750" minimum ☐ Front tire width - .375" minimum ☐ Rear tire diameter - .790" minimum ☐ Rear tire width - .810" maximum ☐ Motor type – JK Hawk Retro / CR 102 ☐ Body height Lotus 49 style - 1.375" maximum ☐ Front wings Lotus 49 style - width across front wings 2.875" maximum. ☐ Body height all others - 1.125" maximum ☐ Front grill - .125" (1/8") ☐ Driver figure/interior - fully-molded, min.2-color, presentably/realistically painted, no paper and attached to the body-no sagging	☐ Total weight - 110 grams minimum ☐ Chassis width - 3.125" Maximum ☐ Body width - 3.250" at the wheel arches ☐ Body thickness - .008" minimum nose with .007" minimum on sides ☐ F & R track width - 3.125" ☐ Chassis clearance, F & R - .015" / .050" minimum ☐ Front tire diameter - .750" minimum ☐ Front tire width - .225" minimum ☐ Rear tire diameter -.8125" minimum ☐ Rear tire width - .810" maximum ☐ Motor type – JK Hawk Retro / CR 102 ☐ Body height - 1.375" maximum ☐ Front grill - .063" (1/16") ☐ Spoiler size / height - no wider than body; .500" maximum ☐ Rear window - painted, tinted, or covered with interior ☐ Driver figure/interior - fully-molded, min.2-color, presentably/realistically painted, no paper and attached to the body-no sagging	☐ Total weight - 120 grams minimum ☐ Chassis width - 3.00" Maximum ☐ Wheelbase - 4.50" ☐ Guide lead - .750" ☐ Body width - 3.250" at the wheel arches ☐ Body thickness - .012" top with .008" minimum on sides/windows, no tape. Min weight 10 grams. ☐ VFC Charger - .210" from top of front fender others on cut lines ☐ Rear fenders may be trimmed for fire clearance. ☐ Rear height- Charger bodies Max. 1.375" ☐ Daytona bodies Max. 1.00 ☐ Rear panel/ bumper dimension Chargers min. .750", Daytona min. .500" ☐ F & R track width 3.00" Maximum ☐ Chassis clearance, F & R - .050" / .050" minimum ☐ Front & rear tire diameter - .8125" minimum ☐ Front tire width - .375" minimum ☐ Rear tire width - .810" maximum ☐ Motor type – JK Hawk Retro / CR 102 ☐ Driver figure/ interior - fully-molded, min. 2-color, presentably/realistically painted, no paper, must be attached to the body no-sagging.

Tech Sheet

Name _____ Raceway _____ Date _____

I hereby grant permission to the IRRA® to use information from this form and any pictures taken during this event on websites, social media, or in print to promote, document, and publicize IRRA® racing and this event. 9/1/2026